



Pro Audio



T 12P

Dual 12" Line Array Full Range System

Features:

- More loudspeakers can be connected vertically to form a line array loudspeaker system
- Available in 90° and 150° horizontal coverage configuration
- Compact dimensions, High power capacity



Technical Specifications:

Technical Parameters	T12P
Frequency Response	HF: 1KHz-20KHz±3dB LMF: 55Hz-1.2KHz±3dB
Components	2×75mm Voice coil Neodymium HF driver 2×12" 88mm Voice coil Neodymium LF driver
Recommended Amplifier	HF: 220W*2 LMF: 1400W*2
Nominal Impedance	HF: 16Ω*2 LMF: 16Ω*2
Coverage	T12P-905 90° Hor/0-5° Ver, 1° increment T12P-930 90° Hor/0-30° Ver, 1° increment T12P-1505 150° Hor/0-5° Ver, 1° increment T12P-1530 150° Hor/0-30° Ver, 1° increment
Sensitivity (1W/1M)	HF: 118dB LMF: 106dB
Maximum SPL (1M)	HF: 145dB, LMF: 142dB
Connectors	2×Neutrik NL-8
Installation manner	Flying or ground stacking (ground-stack frame needed, or stacking on the subwoofer)
Dimension (WxHxD)	926mm x 347mm x 563mm
Weight	58Kg