



📌 TANG475CH

Built-in DSP power amplifier



Technical Specifications:

In/Outputs	Input Channels	2×Analog Inputs	
	Input Connectors	RCA	
	Output Channels	4×Analog Outputs	
Specifications	Frequency Response	20Hz–20kHz	
	Dynamic Range	114dB	
	AD Converters	24bit	
	Sampling Rate	48kHz	
	Input Channels	EQ, FIR filters	
	Output Channels	Gain adjust, independent delay, EQ, IIR crossover	
	FIR Filters	2×FIR filters	
Power Supply	Power Supply	100-240V~50-60Hz	
Input/Output	Output Power	8Ω	4×75W
		4Ω	4×150W
	Input Connector	RCA	
	Output Connector	Phoenix connector	
	Input Sensitivity (dB)	26dB	
Specifications	Power Supply	AC 220V ~ 50-60Hz	
	Input Impedance Balanced	13KΩ	
	Frequency Response	10Hz-30kHz(±1dB) @1W,8Ω	
	THD	< 0.1%	
	Signal/Noise Ratio (dB)	>80 dB	
	Weight	7.5kg	
Protect	Dimensions(W×D×H)	240mm×336mm×85mm	
	Short-circuit, Over-load, Over-heat Protection		