





## **WA 152-7**

Ultra-wide Coverage Full Range Loudspeaker

15" Full range loudspeaker.150° Ultra-wide horizontal coverage.



## **Technical Specifications:**

| Technical Parameters WA152-7  Frequency Response 50 Hz -18KHz±3dB  Coverage Hor: 150°, Ver: 70°  Components 15" 75mm Voice coil High-sensitivity Neodymium LF driver *1 3" voice coil Neodymium HF driver *1  Recommended Amplifier 1200W  Nominal Impedance 8Ω  Sensitivity (1W/1M) 101dB  Max. SPL * 135dB  Connectors 2×NEUTRIK NL-4  Installation recovers |                       |   |
|--|-----------------------|---|
| Coverage Hor: $150^{\circ}$ , Ver: $70^{\circ}$ Components $15^{\circ}$ 75mm Voice coil High-sensitivity Neodymium LF driver *1  Recommended Amplifier $1200W$ Nominal Impedance $8\Omega$ Sensitivity (1W/1M) $101dB$ Max. SPL * $135dB$ Connectors $2 \times NEUTRIK NL-4$ Bracket seat *1 Pre-embedded M8 flying puts *12                                   | Technical Parameters  | WA152-7   |
| Components  15" 75mm Voice coil High-sensitivity Neodymium LF driver *1 3" voice coil Neodymium HF driver *1 1200W  Nominal Impedance 8Ω  Sensitivity (1W/1M) 101dB  Max. SPL * 135dB  Connectors 2×NEUTRIK NL-4  Bracket seat *1 Pre-embedded M8 flying nuts *12  | Frequency Response    | 50 Hz -18KHz±3dB  |
| Sensitivity (1W/1M)   SPL  | Coverage              | Hor: 150°, Ver: 70°   |
| Sensitivity (1W/1M)   101dB  | Components            | 15" 75mm Voice coil High-sensitivity Neodymium LF driver *1 |
| Nominal Impedance 8Ω Sensitivity (1W/1M) 101dB Max. SPL * 135dB Connectors 2×NEUTRIK NL-4 Bracket seat *1 Pre-embedded M8 flying nuts *12  |                       | 3" voice coil Neodymium HF driver *1                        |
| Sensitivity (1W/1M) 101dB  Max. SPL * 135dB  Connectors 2×NEUTRIK NL-4  Bracket seat *1 Pre-embedded M8 flying nuts *12  | Recommended Amplifier | 1200W   |
| Max. SPL * 135dB  Connectors 2×NEUTRIK NL-4  Bracket seat *1 Pre-embedded M8 flying nuts *12   | Nominal Impedance     | 8Ω  |
| Connectors 2×NEUTRIK NL-4  Bracket seat *1 Pre-embedded M8 flying nuts *12   | Sensitivity (1W/1M)   | 101dB   |
| Bracket seat *1 Pre-embedded M8 flying nuts *12  | Max. SPL *            | 135dB   |
| Bracket seat *1, Pre-embedded M8 flying nuts *12,  | Connectors            | 2×NEUTRIK NL-4  |
|  | Installation manner   | Bracket seat *1, Pre-embedded M8 flying nuts *12,           |
| top and bottom with fast flying slots.   |                       | top and bottom with fast flying slots.                      |
| Dimension (H×W×D) 714mm×420mm×360mm  | Dimension (H×W×D)     | 714mm×420mm×360mm   |
| Weight 27Kg  | Weight                | 27Kg  |