



专业音响



TANG 30

Power Amplifier

功能特点:

- 2-Channel Power Amplifier
- High Output and Reliability
- Very high power output/dimension ratio
- Excellent sound quality



Specifications:

Input/Output	Output Power	Stereo	8Ω	2X1050W
			4Ω	2X1500W
		Bridge	8Ω	3000W
	Input Connector		XLR	
	Output Connector		SPEAKON&Binding	
	Separation degree at rated output power of 8Ω 1KHz			62dB
Specifications	Power Supply			AC220-230V ~ 50-60Hz
	Input Impedance	Balanced		20KΩ
		Unbalanced		10KΩ
	Frequency Response			20Hz-20KHz-3dB~ +0.5dB
	THD			≤ 0.02%
	Signal/Noise Ratio(dB)			≥ 100dB
	Conversion Rate			15V/uS
	Damping Factor f=1KHz 8ohms			> 300
	Voltage gain			26dB/27.5dB/28dB/29.5dB/30dB/31dB/36.5dB/40.5dB
	Cooling system			Two steps speed fan
	Net Weight			13.7kg
	Dimensions(WxDxH)			482x315×88mm
Protect	Soft Start,Short Circuit,Limiter,DC Fault,AC Line Fuse,Thermal Cut			