



## 📌 TANG 40

Power Amplifier

### 功能特点:

- 📌 2-Channel Power Amplifier
- 📌 High Output and Reliability
- 📌 Very high power output/dimension ratio
- 📌 Excellent sound quality



### Specifications:

|                                                    |                                                                    |            |              |                                                 |
|----------------------------------------------------|--------------------------------------------------------------------|------------|--------------|-------------------------------------------------|
| Input/Output                                       | Output Power                                                       | Stereo     | 8Ω           | 2X1500W                                         |
|                                                    |                                                                    |            | 4Ω           | 2X2250W                                         |
|                                                    |                                                                    | Bridge     | 8Ω           | 4500W                                           |
|                                                    | Input Connector                                                    |            |              | XLR                                             |
|                                                    | Output Connector                                                   |            |              | SPEAKON&Binding                                 |
| Separation degree at rated output power of 8Ω 1KHz |                                                                    |            |              | 62dB                                            |
| Specifications                                     | Power Supply                                                       |            |              | AC220-230V ~ 50-60Hz                            |
|                                                    | Input Impedance                                                    | Balanced   |              | 20KΩ                                            |
|                                                    |                                                                    | Unbalanced |              | 10KΩ                                            |
|                                                    | Frequency Response                                                 |            |              | 20Hz-20KHz-3dB~+0.5dB                           |
|                                                    | THD                                                                |            |              | ≤ 0.02%                                         |
|                                                    | Signal/Noise Ratio(dB)                                             |            |              | ≥ 100dB                                         |
|                                                    | Conversion Rate                                                    |            |              | 15V/uS                                          |
|                                                    | Damping Factor f=1KHz 8ohms                                        |            |              | > 300                                           |
|                                                    | Voltage gain                                                       |            |              | 26dB/27.5dB/28dB/29.5dB/30dB/31dB/36.5dB/40.5dB |
|                                                    | Cooling system                                                     |            |              | Two steps speed fan                             |
|                                                    | Net Weight                                                         |            |              | 15.6kg                                          |
| Dimensions(WxDxH)                                  |                                                                    |            | 482x315×88mm |                                                 |
| Protect                                            | Soft Start.Short Circuit.Limiter.DC Fault.AC Line Fuse.Thermal Cut |            |              |                                                 |