



↙ DAD12M

Line Array Speaker

Features:

- 🔍 Very high SPL with a longer throw HF coverage.
- 🔍 High power handling capacity.
- 🔍 3-way line array speaker.



Technical Specifications:

Technical Parameters	DAD12M
Components	HF: 10×1" throat 1.5" voice coil Neodymium HF driver MF: 4×6.5" 44mm voice coil Neodymium MF driver LF: 2×12" 100mm voice coil Neodymium LF driver
Continuous Program Power (single cabinet)	HF:700W/6.4Ω MF:1600W/8Ω LF1:2000W/8Ω、LF2:2000W/8Ω、
Nominal Impedance	HF: 6.4Ω MF: 8Ω LF1: 8Ω、LF2: 8Ω
Frequency Response	HF: 1200Hz-20kHz MF: 200Hz-1200Hz LF: 45Hz -200Hz
Coverage	Hor: 50° , 70° , 90° , 110° , 130° optional (symmetric) Ver: 0° -10° in 1° step (0.5° first step) Dependent upon the number of elements and the line source curvature
Sensitivity (1W/1M)	HF50°: 115dB、HF70°: 114 dB、HF90°: 114dB、HF110°: 113dB、HF130°: 113dB MF: 104dB LF1: 95dB、LF2: 95dB
Maximum SPL (1M)	* 146dB
Connectors	YYH-8PA, YYH-8PB; HF:G+,H-、MF: E+,F-、LF1:A+,B-、LF2:C+,D-
Installation manner	Flying or ground stacking (ground-stack frame needed, or stacking on the subwoofer)
Dimension (W×H×D)	1144mm x 380mm x 492mm
Weight	80Kg